

BEHR

SOLID COLOR

CONCRETE *Stain*



SILICONIZED 100% ACRYLIC

***Patios • Walkways & Driveways
Basements • Pool & Cool Decks***



820 CORAL REEF ^W




831 ROSELLE ^W



807 BRICK RED ^D



839 PEACH WHITE ^W



812 GEORGIA PEACH ^W



841 NUEVO TERRA ^W



842 FIRETHORN ^D



832 TANSTONE ^W



817 HARVEST WHEAT ^W



822 BERMUDA TAN ^W



833 CORONADO ^D



834 GRAIN ^W



821 GOLDEN CLAY ^W



802 DESERT SANDSTONE ^W



835 SADDLEBACK ^D



836 NEW WHITE ^W



816 FAWN ^W



837 NEUTRAL TAN ^W



809 CHESTNUT BROWN ^D

Computerized color match to nearly any color!

CONCRETE STAIN



811 WHITE CLOUD ^W



819 CATALINA STONE ^W



806 PEBBLE GRAY ^W



838 TAUPE GRAY ^W



810 GLACIER BLUE ^W



814 BRAZIL MARBLE ^W



808 FOREST GREEN ^D



844 PARK GREEN ^D



Driveway & Walkway: 816 Fawn



848 VERDE TEAL ^D



851 NEW GALAXY ^D



815 PACIFIC FOG ^W



818 SILVER SPUR ^W



801 NATURAL SLATE ^W



852 GUN METAL ^D

Color chips are affected to some degree by the type of light in which they are viewed, exposure to heat, sunlight and the age of the chip itself. Occasionally, there may be a slight difference between the actual stained surface and the color and sheen of the chip shown.



SOLID COLOR CONCRETE Stain

BEHR® SOLID COLOR CONCRETE STAIN is designed to protect and beautify concrete surfaces.

- Siliconized 100% acrylic formula
- Durable solid color stain
- Water repellent
- Formulated for interior & exterior concrete floors
- Available in 40 custom colors and computerized color matching

IDEAL FOR:

Concrete Walls, Basements, Patios, Sidewalks, Driveways, Garage Floors, Pool Decks, Cool Decks & Tennis Courts.

THE IDEAL FINISH REQUIRES PROPER PREPARATION

CLEAN



ETCH



PRIME



UNCOATED SURFACES

CLEAN

- Remove dirt, oil and grease stains with BEHR NO. 990 CONCRETE CLEANER & DEGREASER.

ETCH

- Open surface porosity using BEHR NO. 991 CONCRETE ETCHER & RUST REMOVER.

PRIME

- Apply BEHR NO. 880 CONCRETE BONDING PRIMER to increase adhesion of topcoats to the surface.

TOPCOAT

- Apply BEHR SOLID COLOR CONCRETE STAIN.

COVER PHOTO: 812 Georgia Peach

PREVIOUSLY COATED SURFACES

PREPARE & CLEAN

- Remove any loose or peeling paint and scuff sand the surface.
- Remove dirt, oil and grease stains with BEHR NO. 990 CONCRETE CLEANER & DEGREASER.

ETCH

- Etch any bare concrete with BEHR NO. 991 CONCRETE ETCHER & RUST REMOVER.

PRIME

- Prime all bare areas with BEHR NO. 880 CONCRETE BONDING PRIMER to increase adhesion of topcoats to the surface.

TOPCOAT

- Apply BEHR SOLID COLOR CONCRETE STAIN.

Refer to all product labels for specific instructions.



A Masco Company

©2005 BEHR PROCESS CORPORATION
3400 W. Segerstrom Avenue
Santa Ana, CA 92704 U.S.A. • www.behr.com



C-20

Item No. 931430

7/05

To consult with a Behr Certified Coatings Professional, call 1-800-854-0133, Ext. 2 (U.S.); 1-800-661-1591 (Canada Only) or visit us at www.behr.com